

CLAIMS

Sub B 1. A data management method for managing access to a storage system by at least two devices coupled to the storage system, the method comprising a step of:
selectively servicing, at the storage system, a request from one of the at least two devices
5 for access to a portion of data stored at the storage system responsive to configuration data indicating that the one of the at least two devices is authorized to access the portion of data.

2. The data management method according to claim 1, where the storage system is arranged to store a plurality of volumes of data, and wherein the configuration data is stored in the storage
10 system in a configuration table comprising a plurality of records, each of the records including an identifier and information indicating which of the volumes of data are available to a device associated with the corresponding identifier, and wherein the step of selectively servicing further includes steps of:

receiving the request at the storage system issued by the one of the at least two devices,
15 the request including a source identifier identifying the one of at the at least two devices that initiated the request and an address to one of the volumes of the plurality of volumes in the storage system; and

determining whether to service the request responsive to a portion of the configuration data associated with the source identifier and the address of the one of the volumes.

20 Sub B2 3. The data management method according to claim 1, wherein the storage system and the at least two devices are coupled together by a network, the method including a step of:
forwarding the request from the one of the at least two devices to the storage system over
the network.

25 4. The data management method according to claim 3, wherein the step of forwarding includes forwarding the request using a Fibre Channel protocol.

5. The data management method according to claim 2, further comprising a step of:
30 authenticating the request received at the storage system to verify that the device identified in the source identifier is the one of the at least two devices that issued the request.

6. The data management method according to claim 5, wherein the step of authenticating further comprises a step of comparing an expected identifier associated with the request against an authenticating identifier received with the request to determine whether the expected identifier and authenticating identifier match.

5

7. The data management method according to claim 6, wherein the authenticating identifier is encrypted using a key associated with the one of the at least two devices that issued the request.

10 8. The data management method according to claim 7, wherein the step of authenticating further comprises a step of:

decrypting a portion of the request at the storage system using a key associated with the one of the at least two devices that issued the request.

15 9. The data management method according to claim 1, wherein the one of the at least two devices is a host processor, and wherein the step of forwarding includes the step of forwarding the request from the host processor to the storage system.

20 10. The data management method according to claim 1, wherein at least one of the at least two devices is a file server and wherein the step of forwarding includes the step of forwarding the request from the file server to the storage system.

25 11. The data management method according to claim 1, wherein the storage system includes a plurality of disk drives, and wherein the step of selectively servicing includes the step of forwarding the request to one of the plurality of disk drives.

12. The data management method according to claim 1, further comprising a step of:
validating the request from the one of the at least two devices at the storage system to verify that the request was not altered during transit.

30

09107618-063098
B60E9D"8T9Z0T60

13. The data management method according to claim 2, wherein the configuration table comprises a plurality of records arranged in an array including a plurality of rows corresponding to a number of volumes of data available at the storage system and a plurality of columns corresponding to a number of ports available at the storage system, and wherein each of the records includes a bitmap having a bit corresponding to each device authorized to access each of the corresponding ports, and wherein the step of determining whether to service the request comprises steps of:

indexing the configuration database using the address provided in the request to identify an indexed record; and

comparing the bitmap of the indexed record with the source identifier to determine whether a bit of the bitmap associated with the source identifier indicates that the one of the at least two devices associated with the source identifier has access to the volume of the storage system associated with the indexed record.

14. The data management method according to claim 1, wherein the step of selectively servicing further comprises steps of:

servicing a first request issued by a first one of the at least two devices for access to a first portion of data in the storage system responsive to configuration data associated with the first one of the at least two devices and an address of the first portion of data specified the first

request; and

precluding a second request issued by a second one of the at least two devices for access to the first portion of data in the storage system from being serviced responsive to configuration data associated with the second one of the at least two devices and the address of the first portion of data specified in the second request.

15. A computer readable medium comprising:

a first data structure to manage accesses by a plurality of devices to volumes of data at a storage system, the first data structure comprising a plurality of records corresponding to the plurality of devices, each record of the plurality of records corresponding to one of the plurality of devices and including configuration information identifying which of the volumes of the storage system the one of the plurality of devices is authorized to access.

16. The computer readable medium according to claim 15, in combination with the storage system, wherein the computer readable medium is a memory of the storage system.

Sub B4 5 17. The combination according to claim 16, in further combination with the plurality of devices and a network, wherein the storage system and the plurality of devices are coupled to communicate over the network.

18. The combination of claim 17, wherein the storage system and the plurality of devices communicate according to a Fibre Channel network protocol.

10 19. The combination according to claim 16, wherein the storage system further comprises:
a second data structure comprising a plurality of records that form a copy of a subset of the plurality of records in the first data structure, wherein the subset of the plurality of records in the second data structure is associated with a subset of the plurality of devices that are logged
15 into the storage system.

20. The combination according to claim 19, wherein the second data structure further comprises:

an array of records having a plurality of columns corresponding to the volumes of data at
20 the storage system and a plurality of rows corresponding to a plurality of ports of the storage system, each record in the array including at least one bit corresponding to each of the plurality of devices.

21. A storage system comprising:

Sub B5 25 at least one storage device apportioned into a plurality of volumes;
a configuration table to store configuration data identifying which of a plurality of devices coupled to the storage system are authorized to access each of the plurality of volumes;
and

30 a filter, responsive to the configuration data, to selectively forward to the at least one storage device requests for access to the plurality of volumes received from the plurality of devices.

22. The storage system according to claim 21, wherein the filter forwards a request to a volume for servicing by the storage system responsive to the configuration data indicating that the one of the plurality of devices that issued the request is authorized to access the volume.

23. The storage system according to claim 21, wherein the filter precludes a request to a volume from being serviced by the storage system responsive to the configuration data indicating that the one of the plurality of devices that issued the request is not authorized to access the volume.

24. The storage system according to claim 21, wherein the configuration table comprises a number of records, each record including an identifier and a map, the map indicating which volumes of the storage system are capable of being accessed by a device associated with the identifier, wherein each request received at the filter includes a source identifier identifying the one of the plurality of devices that issued the request and an address to one of the plurality of volumes, and wherein the filter further comprises:

a comparator to compare each request against the information in a selected record in the configuration table associated with the request to determine whether the one of the plurality of devices that issued the request is authorized to access the volume.

25. The storage system according to claim 24, wherein an identifier in the selected record corresponds to the source identifier of the request.

26. The storage system according to claim 21, in combination with the plurality of devices and a network that couples the storage system to the plurality of devices.

27. The combination of claim 26, wherein the storage system and the plurality of devices communicate over the network using a Fibre Channel network protocol.

28. The storage system according to claim 21, further comprising:

means for authenticating each request received at the filter to verify that the one of the plurality of devices indicated in the request as issuing the request is the device that issued the request.

09107618-063098

Seal
B6

29. The storage system according to claim 21, further comprising:
means for validating a request received at the storage system to verify that the request
was not altered in transit.

5 30. The storage system according to claim 21, wherein the at least one storage device
includes a plurality of disk drives.

31. The combination according to claim 26, wherein at least one of the plurality of devices is
a host processor.

10

32. The combination according to claim 26, wherein one of the plurality of devices is a file
server.

09107618 030760
B60E90" BT9/0760